

# SAFETY DATA SHEET

twinbond

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

## TWINBOND FOAM

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : TWINBOND FOAM  
Registration number REACH : Not applicable (mixture)  
Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004  
Degreasing agent

##### 1.2.2 Uses advised against

No uses advised against

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

Twinbond\*  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 25 76 40  
☎ +32 14 22 02 66  
info@novatech.be  
\* Twinbond is a registered trademark of Novatech International N.V.

##### Manufacturer of the product

Novatech International N.V.  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :  
+32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.

#### 2.2. Label elements



**Signal word** Danger

**H-statements**  
H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.

**P-statements**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

#### 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard  
Caution! Substance is absorbed through the skin

# TWINBOND FOAM

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
butane 01-2119474691-32	106-97-8 203-448-7	2.5% ≤C<10%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	
propan-2-ol 01-2119457558-25	67-63-0 200-661-7	2.5% ≤C<10%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent	
propane 01-2119486944-21	74-98-6 200-827-9	2.5% ≤C<10%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
1-methoxy-2-propanol 01-2119457435-35	107-98-2 203-539-1	1%≤C<2.5%	Flam. Liq. 3; H226 STOT SE 3; H336	(1)(2)(10)	Constituent	
isobutane 01-2119485395-27	75-28-5 200-857-2	0.1%≤C<1%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	

- (1) For H- and EUH-statements in full: see section 16  
(2) Substance with a Community workplace exposure limit  
(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006  
(21) 1,3-butadiene <0.1%

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

If you feel unwell, consult a doctor/medical service.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water.

#### After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

No effects known.

##### After skin contact:

No effects known.

##### After eye contact:

No effects known.

##### After ingestion:

No effects known.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

### 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

Reason for revision: 3.2; 8; 15

Publication date: 2000-09-16

Date of revision: 2024-04-16

Revision number: 1200

BIG number: 32180

2 / 18

# TWINBOND FOAM

## 5.3. Advice for firefighters

### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion.

### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Exposure to fire/heat: keep upwind. Exposure to fire/heat: have neighbourhood close doors and windows.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

### 6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Keep container tightly closed.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Protect against frost. Keep out of direct sunlight. Keep container in a well-ventilated place. Fireproof storeroom.

#### 7.2.2 Keep away from:

Heat sources, ignition sources.

#### 7.2.3 Suitable packaging material:

Aerosol.

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

#### EU

1-Methoxypropanol-2	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	100 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	375 mg/m <sup>3</sup>
	Short time value (Indicative occupational exposure limit value)	150 ppm
	Short time value (Indicative occupational exposure limit value)	568 mg/m <sup>3</sup>

# TWINBOND FOAM

## Belgium

1-Méthoxy-2-propanol	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	184 mg/m <sup>3</sup>
	Short time value	100 ppm
	Short time value	369 mg/m <sup>3</sup>
Alcool isopropylique	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	500 mg/m <sup>3</sup>
	Short time value	400 ppm
	Short time value	1000 mg/m <sup>3</sup>
Butane, tous isomères: iso-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Butane, tous isomères: n-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm

## The Netherlands

1-Methoxy-2-propanol	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	100 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	375 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	150 ppm
	Short time value (Public occupational exposure limit value)	563 mg/m <sup>3</sup>

## France

1-Méthoxy-2-propanol	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	50 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	188 mg/m <sup>3</sup>
	Short time value (VRC: Valeur réglementaire contraignante)	100 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	375 mg/m <sup>3</sup>
Alcool isopropylique	Short time value (VL: Valeur non réglementaire indicative)	400 ppm
	Short time value (VL: Valeur non réglementaire indicative)	980 mg/m <sup>3</sup>
n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m <sup>3</sup>

## Germany

1-Methoxy-2-propanol	Time-weighted average exposure limit 8 h (TRGS 900)	100 ppm <b>(1)</b>
	Time-weighted average exposure limit 8 h (TRGS 900)	370 mg/m <sup>3</sup> <b>(1)</b>
Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm <b>(2)</b>
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup> <b>(2)</b>
Isobutan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm <b>(2)</b>
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup> <b>(2)</b>
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm <b>(2)</b>
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m <sup>3</sup> <b>(2)</b>
Propan-2-ol	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm <b>(3)</b>
	Time-weighted average exposure limit 8 h (TRGS 900)	500 mg/m <sup>3</sup> <b>(3)</b>

(1) UF: 2 (I)

(2) UF: 4 (II)

(3) UF: 2 (II)

# TWINBOND FOAM

## Austria

1-Methoxypropanol-2	Tagesmittelwert (MAK)	50 ppm
	Tagesmittelwert (MAK)	187 mg/m <sup>3</sup>
	Kurzzeitwert Mow (MAK)	50 ppm
	Kurzzeitwert Mow (MAK)	187 mg/m <sup>3</sup>
2-Propanol Kurzzeitwert für Großguss	*) Kurzzeitwert für Großguss gilt bis 31.12.2013	
	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	500 mg/m <sup>3</sup>
	Kurzzeitwert 30(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 30(Miw) 4x (MAK)	2000 mg/m <sup>3</sup>
2-Propanol	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	500 mg/m <sup>3</sup>
	Kurzzeitwert 15(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	2000 mg/m <sup>3</sup>
Butan (beide Isomeren): n-Butan (R 600) Isobutan (R 600a)	Tagesmittelwert (MAK)	800 ppm
	Tagesmittelwert (MAK)	
	Tagesmittelwert (MAK)	1900 mg/m <sup>3</sup>
	Tagesmittelwert (MAK)	
	Kurzzeitwert 60(Mow) 3x (MAK)	1600 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	
	Kurzzeitwert 60(Mow) 3x (MAK)	3800 mg/m <sup>3</sup>
	Kurzzeitwert 60(Mow) 3x (MAK)	
Propan (R 290)	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1800 mg/m <sup>3</sup>
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3600 mg/m <sup>3</sup>

## UK

1-Methoxypropan-2-ol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	100 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	375 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	150 ppm
	Short time value (Workplace exposure limit (EH40/2005))	560 mg/m <sup>3</sup>
Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m <sup>3</sup>
Propan-2-ol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	999 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1250 mg/m <sup>3</sup>

# TWINBOND FOAM

## Denmark

1-Methoxy-2-propanol	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	185 mg/m <sup>3</sup>
	Short time value	150 ppm
	Short time value	568 mg/m <sup>3</sup>
Isopropylalkohol	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	490 mg/m <sup>3</sup>
	Short time value	400 ppm (1)
	Short time value	980 mg/m <sup>3</sup> (1)
n-Butan	Time-weighted average exposure limit 8 h	500 ppm
	Time-weighted average exposure limit 8 h	1200 mg/m <sup>3</sup>
	Short time value	1000 ppm (1)
	Short time value	2400 mg/m <sup>3</sup> (1)
Propan	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1800 mg/m <sup>3</sup>
	Short time value	2000 ppm (1)
	Short time value	3600 mg/m <sup>3</sup> (1)

(1) Jf. § 3, stk. 2

## USA (TLV-ACGIH)

1-Methoxy-2-propanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	50 ppm
	Short time value (TLV - Adopted Value)	100 ppm
2-propanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
	Short time value (TLV - Adopted Value)	400 ppm
Butane, isomers	Short time value (TLV - Adopted Value)	1000 ppm
	Short time value (TLV - Adopted Value)	
Explosion hazard		
Propane	See Appendix F: Minimal Oxygen Content; Simple asphyxiant, Explosion hazard	

## b) National biological limit values

If limit values are applicable and available these will be listed below.

### Germany

1-Methoxypropan-2-ol (1-Methoxypropan-2-ol)	Urin: expositionsende, bzw. schichtende	15 mg/l	
Propan-2-ol (Aceton)	Urin: expositionsende, bzw. schichtende	25 mg/l	
Propan-2-ol (Aceton)	Vollblut: expositionsende, bzw. schichtende	25 mg/l	

### USA (BEI-ACGIH)

2-Propanol (Acetone)	Urine: end of shift at end of workweek	40 mg/L	Background, Nonspecific
----------------------	--	---------	-------------------------

## 8.1.2 Sampling methods

Product name	Test	Number
1-Methoxy-2-Propanol	OSHA	99
Isopropanol (Volatile Organic compounds)	NIOSH	2549
Isopropyl Alcohol (Alcohols I)	NIOSH	1400
Isopropyl Alcohol	NIOSH	3900
Isopropyl Alcohol	OSHA	5001
Propylene glycol monomethyl ether (glycol ethers)	NIOSH	2554

## 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

## 8.1.4 Threshold values

### DNEL/DMEL - Workers

#### propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	500 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	888 mg/kg bw/day	

#### 1-methoxy-2-propanol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	369 mg/m <sup>3</sup>	
	Acute systemic effects inhalation	553.5 mg/m <sup>3</sup>	
	Acute local effects inhalation	553.5 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	183 mg/m <sup>3</sup>	

### DNEL/DMEL - General population

#### propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	89 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	319 mg/kg bw/day	
	Long-term systemic effects oral	26 mg/kg bw/day	

Reason for revision: 3.2; 8; 15

Publication date: 2000-09-16

Date of revision: 2024-04-16

Revision number: 1200

BIG number: 32180

6 / 18

# TWINBOND FOAM

## 1-methoxy-2-propanol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	43.9 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	78 mg/kg bw/day	
	Long-term systemic effects oral	33 mg/kg bw/day	

## PNEC

### 1-methoxy-2-propanol

Compartment	Value	Remark
Fresh water	10 mg/l	
Fresh water (intermittent releases)	100 mg/l	
Marine water	1 mg/l	
STP	100 mg/l	
Fresh water sediment	52.3 mg/kg sediment dw	
Marine water sediment	5.2 mg/kg sediment dw	
Soil	4.59 mg/kg soil dw	

### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

#### c) Eye protection:

Protective goggles (EN 166).

#### d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

### 8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Colour	Colourless
Odour	Alcohol odour
Odour threshold	No data available in the literature
Melting point	No data available in the literature
Boiling point	No data available in the literature
Flammability	Extremely flammable aerosol.
Explosion limits	1.5 - 13.7 vol %
Flash point	Not applicable (aerosol)
Auto-ignition temperature	Not applicable (aerosol)
Decomposition temperature	No data available in the literature
pH	No data available in the literature
Kinematic viscosity	Not applicable (aerosol)
Dynamic viscosity	Not applicable (aerosol)
Solubility	Water ; soluble
Log Kow	Not applicable (mixture)
Vapour pressure	No data available in the literature
Absolute density	0.946 kg/m <sup>3</sup> ; 20 °C ; Liquid
Relative density	0.94 ; 20 °C ; Liquid
Relative vapour density	> 1
Particle size	No data available in the literature

### 9.2. Other information

No data available

# TWINBOND FOAM

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

#### Precautionary measures

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

Upon combustion: CO and CO<sub>2</sub> are formed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

#### Acute toxicity

##### TWINBOND FOAM

No (test)data on the mixture available

Judgement is based on the relevant ingredients

##### propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	5840 mg/kg bw		Rat	Experimental value	
Dermal	LD50	Equivalent to OECD 402	16400 ml/kg bw	24 h	Rabbit	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 10000 ppm	6 h	Rat (male / female)	Experimental value	

##### 1-methoxy-2-propanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	EU Method B.1 tris	4016 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to EU Method B.3	> 2000 mg/kg bw	24 h	Rat (male / female)	Experimental value	
Inhalation (vapours)	LC0	Equivalent to OECD 403	> 7000 ppm	6 h	Rat (male / female)	Experimental value	

#### Conclusion

Not classified for acute toxicity

#### Corrosion/irritation

##### TWINBOND FOAM

No (test)data on the mixture available

Judgement is based on the relevant ingredients

##### propan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		1; 2; 3; 4; 7; 10; 14 days	Rabbit	Experimental value	Single treatment without rinsing
Skin	Not irritating		4 h	4; 24; 48; 72 hours	Rabbit	Experimental value	

##### 1-methoxy-2-propanol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to EU Method B.5		24; 48; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Skin	Not irritating	Equivalent to EU Method B.4	4 h	24; 48; 72 hours	Rabbit	Experimental value	

#### Conclusion

Reason for revision: 3.2; 8; 15

Publication date: 2000-09-16

Date of revision: 2024-04-16

Revision number: 1200

BIG number: 32180

8 / 18



# TWINBOND FOAM

Not classified as irritating to the skin  
 Not classified as irritating to the eyes  
 Not classified as irritating to the respiratory system

## Respiratory or skin sensitisation

### TWINBOND FOAM

No (test)data on the mixture available  
 Judgement is based on the relevant ingredients  
propan-2-ol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Dermal	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

### 1-methoxy-2-propanol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to EU Method B.6			Guinea pig (male / female)	Experimental value	
Skin	Not sensitizing	Equivalent to method of Maguire (1973)		24; 48 hours	Guinea pig (male)	Experimental value	

### Conclusion

Not classified as sensitizing for skin  
 Not classified as sensitizing for inhalation

## Specific target organ toxicity

### TWINBOND FOAM

No (test)data on the mixture available  
 Judgement is based on the relevant ingredients  
propan-2-ol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral							Data waiving	
Dermal							Data waiving	
Inhalation (vapours)	NOAEC	OECD 451	5000 ppm	No adverse systemic effects	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	
Inhalation (vapours)	Dose level	Equivalent to OECD 403	5000 ppm	Central nervous system (drowsiness, dizziness)	6 h	Rat (male / female)	Experimental value	

### 1-methoxy-2-propanol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL	Equivalent to OECD 407	919 mg/kg bw/day	No effect	7 weeks (5 days / week)	Rat (male)	Experimental value	
Oral (stomach tube)	NOAEL	Equivalent to OECD 407	2757 mg/kg bw/day	Overall effects	7 weeks (5 days / week)	Rat (male)	Experimental value	
Dermal	NOAEL	Equivalent to OECD 410	> 1000 mg/kg bw/day	No effect	3 weeks (5 days / week)	Rabbit (male / female)	Experimental value	
Inhalation (vapours)	NOAEL	Equivalent to OECD 413	1000 ppm	No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	
Inhalation	Dose level	Human observation	1000 ppm	Central nervous system depression	≤ 7 h	Human	Experimental value	

### Conclusion

Not classified for subchronic toxicity

## Mutagenicity (in vitro)

### TWINBOND FOAM

No (test)data on the mixture available  
 Judgement is based on the relevant ingredients

Reason for revision: 3.2; 8; 15

Publication date: 2000-09-16

Date of revision: 2024-04-16

Revision number: 1200

BIG number: 32180

9 / 18

# TWINBOND FOAM

## propan-2-ol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value	

## 1-methoxy-2-propanol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative without metabolic activation	Equivalent to OECD 476	Chinese hamster lung fibroblasts (V79)	No effect	Experimental value	

## Mutagenicity (in vivo)

### TWINBOND FOAM

No (test)data on the mixture available

Judgement is based on the relevant ingredients

#### propan-2-ol

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male / female)	No effect	Experimental value	Single intraperitoneal injection

#### 1-methoxy-2-propanol

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male / female)	No effect	Experimental value	Single intraperitoneal injection

### Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

### TWINBOND FOAM

No (test)data on the mixture available

Judgement is based on the relevant ingredients

#### propan-2-ol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Inhalation (vapours)	NOEL	OECD 451	5000 ppm	No carcinogenic effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	

#### 1-methoxy-2-propanol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Inhalation (vapours)	NOEL	OECD 453	3000 ppm	No carcinogenic effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	

### Conclusion

Not classified for carcinogenicity

## Reproductive toxicity

### TWINBOND FOAM

No (test)data on the mixture available

Judgement is based on the relevant ingredients

# TWINBOND FOAM

## propan-2-ol

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	Foetus (no effect)	Experimental value	
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect	Experimental value	
Effects on fertility (Oral (drinking water))	NOAEL	Equivalent to OECD 415	853 mg/kg bw/day		Rat (male / female)	No effect	Experimental value	

## 1-methoxy-2-propanol

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Inhalation)	NOAEL	Equivalent to OECD 414	1500 ppm	10 days (6h / day)	Rat	No effect	Experimental value	
Maternal toxicity (Inhalation)	NOAEL	Equivalent to OECD 414	1500 ppm	10 days (6h / day)	Rat	No effect	Experimental value	
Effects on fertility (Inhalation (vapours))	NOAEL (P)	OECD 416	300 ppm		Rat (male / female)	No effect	Experimental value	

### Conclusion

Not classified for reprotoxic or developmental toxicity

### Aspiration hazard

#### TWINBOND FOAM

Judgement is based on the relevant ingredients  
Not classified for aspiration toxicity

### Toxicity other effects

#### TWINBOND FOAM

##### 1-methoxy-2-propanol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Inhalation (vapours)				Central nervous system (drowsiness)			Literature study	

### Chronic effects from short and long-term exposure

#### TWINBOND FOAM

No effects known.

### 11.2. Information on other hazards

No evidence of endocrine disrupting properties

## SECTION 12: Ecological information

### 12.1. Toxicity

#### TWINBOND FOAM

No (test) data on the mixture available  
Judgement of the mixture is based on the relevant ingredients

# TWINBOND FOAM

## propan-2-ol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	9640 mg/l - 10000 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	LC50	Equivalent to OECD 202	> 10000 mg/l	24 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	Toxicity threshold		1800 mg/l	7 day(s)	Scenedesmus quadricauda	Static system	Fresh water	Experimental value; Toxicity test
Long-term toxicity fish	NOELR	Petrotox computer model	> 1000 mg/l	28 day(s)	Brachydanio rerio			Estimated value
Long-term toxicity aquatic crustacea	NOEC		141 mg/l	16 day(s)	Daphnia magna		Fresh water	Experimental value; Growth
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	1050 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Toxicity test
	EC50	ISO 8192	41676 mg/l	30 minutes	Activated sludge			Experimental value

## 1-methoxy-2-propanol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	≥ 1000 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	LC50	ESR-ES-15	21100 mg/l - 25900 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50		> 1000 mg/l	7 day(s)	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity aquatic micro-organisms	IC50	OECD 209	> 1000 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value; GLP

## Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

## 12.2. Persistence and degradability

### propan-2-ol

#### Biodegradation water

Method	Value	Duration	Value determination
EU Method C.5	53 %; Oxygen consumption	5 day(s)	Experimental value

#### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	17.668 h	1.5E6 /cm <sup>3</sup>	Calculated value

### 1-methoxy-2-propanol

#### Biodegradation water

Method	Value	Duration	Value determination
OECD 301E	96 %; GLP	28 day(s)	Experimental value

#### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	7.8 h	1.5E6 /cm <sup>3</sup>	Calculated value

## Conclusion

### Water

The surfactant(s) is/are biodegradable according to Regulation (EC) No 648/2004  
Contains non readily biodegradable component(s)

## 12.3. Bioaccumulative potential

### TWINBOND FOAM

#### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

# TWINBOND FOAM

propan-2-ol

## BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFBAF v3.01	1015			Estimated value

## Log Kow

Method	Remark	Value	Temperature	Value determination
		0.05	25 °C	Weight of evidence approach

1-methoxy-2-propanol

## Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 117		< 1	20 °C	Experimental value

## Conclusion

Does not contain bioaccumulative component(s)

## 12.4. Mobility in soil

propan-2-ol

### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.185 - 0.541	Calculated value

1-methoxy-2-propanol

### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.15	Calculated value

### Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
	9.4 %	0 %	0.01 %	0.01 %	91 %	Experimental value

## Conclusion

Contains component(s) with potential for mobility in the soil

## 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

## 12.7. Other adverse effects

### TWINBOND FOAM

#### Greenhouse gases

Contains component(s) included in the list of substances which may contribute to the greenhouse effect (IPCC)  
None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

#### Groundwater

Groundwater pollutant

propan-2-ol

#### Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

#### Groundwater

Groundwater pollutant

1-methoxy-2-propanol

#### Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

#### Groundwater

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.  
Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

14 06 03\* (waste organic solvents, refrigerants and foam/aerosol propellants: other solvents and solvent mixtures). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Reason for revision: 3.2; 8; 15

Publication date: 2000-09-16

Date of revision: 2024-04-16

Revision number: 1200

BIG number: 32180

13 / 18

# TWINBOND FOAM

Remove waste in accordance with local and/or national regulations. Specific treatment. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Should not be landfilled with household waste. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

## 13.1.3 Packaging/Container

### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

### Road (ADR)

14.1. UN number or ID number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

### Rail (RID)

14.1. UN number or ID number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Hazard identification number	23
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

### Inland waterways (ADN)

14.1. UN number or ID number	
UN number/ID number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190

Reason for revision: 3.2; 8; 15

Publication date: 2000-09-16

Date of revision: 2024-04-16

Revision number: 1200

BIG number: 32180

14 / 18

# TWINBOND FOAM

Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

## Sea (IMDG/IMSBC)

14.1. UN number or ID number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable

## Air (ICAO-TI/IATA-DGR)

14.1. UN number or ID number	
UN number/ID number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
16 %	
151.6 g/l	

1-methoxy-2-propanol

Product name	Skin resorption
1-Methoxypropanol-2	Skin

Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability

Reason for revision: 3.2; 8; 15

Publication date: 2000-09-16

Date of revision: 2024-04-16

Revision number: 1200

BIG number: 32180

15 / 18

# TWINBOND FOAM

Ingredients according to Regulation (EC) No 648/2004 and amendments

5-15% aliphatic hydrocarbons, <5% perfumes

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· propan-2-ol · 1-methoxy-2-propanol	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: “Keep lamps filled with this liquid out of the reach of children”; and, by 1 December 2010, “Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage”; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: “Just a sip of grill lighter may lead to life threatening lung damage”; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
· propan-2-ol · 1-methoxy-2-propanol	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — “whoopee” cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: “For professional users only”. 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
· propan-2-ol	Substances falling within one or more of the following points: (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008: — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 — serious eye damage category 1 or eye irritant category 2 (b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council (c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081

Reason for revision: 3.2; 8; 15

Publication date: 2000-09-16

Date of revision: 2024-04-16

Revision number: 1200

BIG number: 32180

16 / 18



# TWINBOND FOAM

(d) substances listed in Appendix 13 to this Annex.  
The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.

## National legislation Belgium

### TWINBOND FOAM

No data available

#### propan-2-ol

Agents cancérogènes, mutagènes et reprotoxiques et aux agents possédant des propriétés perturbant le système endocrinien (Code du bien-être au travail, Livre VI, titre 2)	alcool isopropylique; VI.2.2.; Liste des procédés au cours desquels une substance ou un mélange se dégage; Procédé à l'acide fort dans la fabrication d'alcool isopropylique.
--	---

#### 1-methoxy-2-propanol

Résorption peau	1-Méthoxy-2-propanol; D; La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air.
-----------------	---

## National legislation The Netherlands

### TWINBOND FOAM

Waterbezwaarlijkheid	B (3); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

#### 1-methoxy-2-propanol

Huidopname (wettelijk)	1-Methoxy-2-propanol; H
------------------------	-------------------------

## National legislation France

### TWINBOND FOAM

No data available

#### 1-methoxy-2-propanol

Risque de pénétration percutanée	1-Méthoxy-2-propanol; Risque de pénétration percutanée
----------------------------------	--

## National legislation Germany

### TWINBOND FOAM

Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge
WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017

#### propan-2-ol

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Propan-2-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

#### 1-methoxy-2-propanol

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	1-Methoxy-2-propanol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

## National legislation Austria

### TWINBOND FOAM

No data available

#### 1-methoxy-2-propanol

besondere Gefahr der Hautresorption	1-Methoxypropanol-2; H
-------------------------------------	------------------------

## National legislation United Kingdom

### TWINBOND FOAM

No data available

#### 1-methoxy-2-propanol

Skin absorption	1-Methoxypropan-2-ol; Sk
-----------------	--------------------------

## National legislation Denmark

### TWINBOND FOAM

No data available

#### 1-methoxy-2-propanol

Hudgennemtrængelige stof	1-Methoxy-2-propanol; H
--------------------------	-------------------------

## Other relevant data

### TWINBOND FOAM

No data available

#### propan-2-ol

TLV - Carcinogen	2-propanol; A4
IARC - classification	3; Isopropanol

Reason for revision: 3.2; 8; 15

Publication date: 2000-09-16

Date of revision: 2024-04-16

Revision number: 1200

BIG number: 32180

17 / 18

# TWINBOND FOAM

1-methoxy-2-propanol

TLV - Carcinogen

1-Methoxy-2-propanol; A4

## 15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

## SECTION 16: Other information

### Full text of any H- and EUH-statements referred to under section 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BEI	Biological Exposure Indices
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC10	Effect Concentration 10 %
EC50	Effect Concentration 50 %
ERC50	EC50 in terms of reduction of growth rate
GLP	Good Laboratory Practice
LC0	Lethal Concentration 0 %
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
LOAEC/LOAEL	Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level
NOAEC/NOAEL	No Observed Adverse Effect Concentration/No Observed Adverse Effect Level
NOEC/NOEL	No Observed Effect Concentration/No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3.2; 8; 15

Publication date: 2000-09-16

Date of revision: 2024-04-16

Revision number: 1200

BIG number: 32180

18 / 18